



**Part Number: 8770**

Audio/Control/Instrumentation, (3) 18 AWG 16x30) TC, PE/PVC, Foil Shld, CM

[Request Sample](#)

## Product Description

Three 18 AWG stranded (16x30) tinned copper conductors, conductors cabled, polyethylene insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
18	16x30	TC - Tinned Copper	3

Conductor Count:	3
Conductor Size:	18 AWG

#### Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.018 in

#### Color Chart

Number	Color
1	Black
2	Red
3	Clear

#### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum/Polyester	Beldfoil® with shorting fold	100 %	TC - Tinned Copper	20	Stranded mm

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.246 in	0.033 in

### Construction and Dimensions

#### Cabling

Lay Direction	Twists
Left Hand	4.4 twist/ft

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
6.6 Ohm/1000ft	8.5 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
24 pF/ft	48 pF/ft

Shielding:	Foil(s) or Copper Tape(s)
------------	---------------------------

#### Inductance

Nominal Inductance
--------------------

0.18 µH/ft

#### Impedance

##### Nominal Characteristic Impedance

69 Ohm

#### Current

Element	Max. Recommended Current [A]
10C temperature rise	5.3 Amps per conductor @ 25°C ambient

#### Voltage

##### UL Voltage Rating

300 V RMS

### Temperature Range

UL Temp Rating:	60°C (UL AWM Style 2093)
Operating Temp Range:	-20°C To +60°C

### Mechanical Characteristics

Bulk Cable Weight:	36 lbs/1000ft
Max Recommended Pulling Tension:	74 lbs
Min Bend Radius/Minor Axis:	2.5 in

### Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
UL AWM Style:	UL Style 2093 (300 V 60°C)
CPR Euroclass:	Eca

### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	88770

### Part Number

#### Variants

Item #	Color	Footnote
8770.023048	Black	
8770.00U152	Chrome	
8770.00U305	Chrome	

8770.01152	Chrome	
8770.013048	Chrome	
8770.01305	Chrome	
8770 0601000	Chrome	C
8770 06010000	Chrome	C Y
8770 06012000	Chrome	C Y
8770 060500	Chrome	C
8770 0605000	Chrome	
8770 060U1000	Chrome	
8770 060U500	Chrome	

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Y - FINAL PUT-UP LENGTH MAY VAR -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.